

Cabinet Exhaust Fans With Shutters

Features

- 120V, 1-Phase or 230 / 460V, 3-Phase, ball bearing, permanently lubricated, drip proof motor - UL listed
- Permanently lubricated bearings on blade drive shaft
- Aluminum blade
- Aluminum shutter
- 20 Gauge powder coated venturi
- 18 Gauge galvanized steel housing
- 1725 RPM
- Motor frame size 56 / Shaft: 5/8"
- Ships fully assembled
- Meets OSHA Standards • 1 year warranty



Standard Models

SIZE	MOTOR	AMPS		CFM	WT. (LBS)	115V 1Ph			230 / 460V 3Ph			
		HP	115V			230/460V	UPC# 686334	MODEL		UPC# 686334	MODEL	
24	1/3	5	1.9 / .9	3270	100	868396	CBT-24B		868525	CBT-24B-3		
30	1/3	6	1.9 / .9	7730	120	868402	CBT-30B		868532	CBT-30B-3		
36	1/2	8	2.3 / 1.1	9870	135	868419	CBT-36B		868549	CBT-36B-3		
42	3/4	11	3.3 / 1.5	14800	155	868426	CBT-42B		868556	CBT-42B-3		
48	1	15	3.8 / 1.9	21500	200	868518	CBT-48B		868501	CBT-48B-3		

Dimensions

SIZE	OUTSIDE DIMENSIONS			MAXIMUM REQUIRED INSIDE WALL OPENING
	HEIGHT	WIDTH	DEPTH	
24"	28 1/4"	28 1/4"	22 1/2"	28 3/4" x 28 3/4"
30"	34 1/4"	34 1/4"	22 1/2"	34 1/2" x 34 1/2"
36"	40 1/4"	40 1/4"	18 1/2"	40 1/2" x 40 1/2"
42"	48 1/2"	48 1/2"	18 1/2"	48 3/4" x 48 3/4"
48"	54 1/2"	54 1/2"	21 1/2"	54 3/4" x 54 3/4"